

1000BASE-EX SFP 1310nm 40km MMF

POPULAR COMPATIBILITY OPTIONS

Vendor	Part Code
Cisco	GLC-EX-SMD
Cisco	MGBLH1
Juniper	SFP-1GE-EX-40
HPe	JD061A
Arista	SFP-1G-EX-40
Brocade	E1MG-EX-40
Dell	SFP-LX-4
Extreme	I-MGBIC-GLX-40
Allied Telesis	AT-SPLX40
D-Link	DEM-314G
TRENDnet	TEG-GBS4

1000BASE-EX SPECIFICATIONS

Form Factor	SFP
Data Range	1000Mbs
Tx/Rx Wavelength	1310nm
Compatible	See table on left
Reach	40km
Cable Type	SMF
Interface Type	SMP
DDM/DOM	Yes
Connector Type	Duplex-LC
Power Budget	-9.5-3dBm
Temperature Range	0-70°C
Warranty	Lifetime

75+ other vendors available

TESTING

- Compatibility Tested: Each transceiver is tested in an original host switch for recognition (Loop back test)
- Performance Tested: Tested over an optical connection of the intended distance. Recreated in the lab using a bit fiber spool method
- 100% Testing of all Transceiver- No Batch Testing (1-10%)

1000BASE-EX FEATURES

- Hot pluggable SFP footprint
- Protocol-SFF-8472 IEEE 802.3AH-2004
- Built in digital diagnostic function
- Compliant with OEM Vendor

DESCRIPTION

This 1000BASE-EX compatible SFP transceiver provides 1G-EX throughput up to 40km over Single-mode fiber (SMF) using a wavelength of 1310nm via an LC connector.

It is guaranteed to be 100% compatible with the OEM host switch, router or network interface card (NIC). This easy to install, hot swappable transceiver has been programmed, uniquely serialized and application tested to ensure that it will initialize and perform identically to the OEM Transceiver. Digital optical monitoring (DOM) support is also present to allow access to real-time operating parameters.

We stand behind the quality of our products and proudly offer a lifetime warranty.

