

100G QSFP28 to 4 SFP28 DAC Breakout Cable

100G BREAKOUT DAC SPECIFICATIONS

Form Factor	QSFP28/SFP28
Data Rate	100G/4 x 25G
Compatible	See table on right
Wire AWG	28AWG
Interface Type	QSFP28 - SFP28
DDM/DOM	Yes
Minimum Bend Radius	23mm
Power Supply	3.3V
Temperature Range	0-70°C
Jacket Material	LSZH
Warranty	Lifetime

POPULAR COMPATIBILITY OPTIONS

Vendor	Part Code
Cisco	QSFP-4SF-P25G-CUxM
Juniper	JNP-100G-4X25G-xM
Arista	CAB-Q-4S-xM
Brocade	100G-Q28-S28-C-0x01
Dell	DAC-Q28-4SFP28-25G-x
Extreme	1042x
Huawei	DAC-Q28-S28-xM
H3C	QSFP-4SFP28-CU-xM
D-Link	Avago
Avaya	Ciena

75+ other vendors available

TESTING

- Compatibility Tested: Each DAC is tested in an original host switch for recognition (Loop back test)
- 100% Testing of all Transceivers: No Batch Testing (1-10%)

AVAILABLE LENGTHS

0.5m, 1m, 1.5m, 2m, 2.5m, 3m, 5m, 7m

100G BREAKOUT FEATURES

- Supports 98.4 to 102.5 Gb/s bit rates
- RoHS-6 compliant
- Built-in digital diagnostic function
- Compliant with OEM Vendor multi-source agreement
- Allows high density connections
- Passive Copper Twinax Cable

DESCRIPTION

This is a multi-vendor compatible 100GBase-CU QSFP28 to 4 SFP28 Direct attach breakout cable, that operates over passive copper with a maximum reach of 7.0m. It has been programmed, uniquely serialized, data-traffic and application tested to ensure it is 100% compliant and functional. It is guaranteed to be compatible with the OEM host switch, router or network interface card (NIC).

This Direct Attach Cable is built to comply with MSA (Multi-Source Agreement) standard. Digital Optical Monitoring (DOM) support is also present to allow access to real-time operating parameters.

We stand behind the quality of our products and proudly offer a lifetime warranty.

