

IEC C14-C13 LSZH/LSOH Power Cable

IEC C14-C13 SPECIFICATIONS

Connector A	IEC 60320 C14
Connector B	IEC 60320 C13
Max Ampere	15A
European Designation	H05Z1Z1-F
Conductor Size	1.5mm ²
Number of Conductors	3
Wire AWG	14 AWG
Cable Outer Diameter	9.5 ± 0.2mm
Jacket Temp Rating	105°C
Jacket Colour	Black
Jacket Material	LSZH
Warranty	Lifetime

PRODUCT CODES & STANDARDS

PRODUCT CODES
C14-C13-H05Z1Z1-F-IEC-1M
C14-C13-H05Z1Z1-F-IEC-1.5M
C14-C13-H05Z1Z1-F-IEC-2M
C14-C13-H05Z1Z1-F-IEC-3M
C14-C13-H05Z1Z1-F-IEC-5M
STANDARDS
H05Z1Z1- European LSZH Designation
IEC 60320 – International Standard 3.0
RoHs-6 – Free from Lead

Lifetime warranty – Quality Assured



TESTING

All power cords have been vigorously tested to ensure they are low smoke zero halogen complaint.

AVAILABLE LENGTHS

1m, 1.5m, 2m, 3m, 5m

IEC C14-C13 FEATURES

- The C14 (male) is a plug whereas the C13 (female) is an outlet or socket of the same mating pair format.
- RoHs-6 compliant.
- Compliant with all the industries PDU's and IT equipment such as Switches, Routers and POE Injectors.

DESCRIPTION

This industry universal IEC C14 to C13 Power extension cable, operates with oxygen-free copper conductors for low resistance to increase conductivity and uphold a stable transmission.

All our power cables have been power-traffic and application tested to ensure they are 100% compliant and functional.

They are guaranteed to be compatible with all Power Distribution Units (PDU), Switches, Routers and POE Injectors.

We stand behind the quality of our products and proudly offer a lifetime warranty.