

IEC C20-C19 LSZH/LSOH Power Cable

IEC C20-C19 SPECIFICATIONS

Connector A	IEC 60320 C20
Connector B	IEC 60320 C19
Max Ampere	20A
European Designation	H05Z1Z1-F
Conductor Size	1.5mm ²
Number of Conductors	3
Wire AWG	12 AWG
Cable Outer Diameter	11 ± 0.3mm
Jacket Temp. Rating	105 °C
Jacket Colour	Black
Jacket Material	LSZH
Warranty	Lifetime

PRODUCT CODES & STANDARDS

PRODUCT CODES
C20-C19-H05Z1Z1-F-IEC-1M
C20-C19-H05Z1Z1-F-IEC-1.5M
C20-C19-H05Z1Z1-F-IEC-2M
C20-C19-H05Z1Z1-F-IEC-3M
C20-C19-H05Z1Z1-F-IEC-5M
STANDARDS
H05Z1Z1- European LSZH Designation
IEC 60320 – International Standard 3.0
RoHs-6 – Free from Lead

Lifetime warranty – Quality Assured



TESTING

Each individual cord is performance and quality tested to ensure failure rate is below industry standard.

AVAILABLE LENGTHS

1m, 1.5m, 2m, 2.5m, 3m, 5m

IEC C20-C19 FEATURES

- The C20 (male) is a plug whereas the C19 (female) is an outlet or socket of the same mating pair format.
- RoHs-6 compliant.
- Compliant with all the industries PDU's and UPS's Power Connections.
- Thick 12 AWG wire gauge manages high power levels required for larger equipment.

DESCRIPTION

This industry universal IEC320 C20 to IEC320 C19 Power extension cable, operates with oxygen-free copper conductors for low resistance to increase conductivity and uphold a stable transmission.

All our power cables have been power-traffic and application tested to ensure they are 100% compliant and functional.

They are guaranteed to be compatible with all Power Distribution Units (PDU) and uninterruptible Power Supplies (UPS).

We stand behind the quality of our products and proudly offer a lifetime warranty.